


Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
 Reference number: 093A
 Revision date: 21/12/2022
 Supersedes version of: 29/07/2021
 Version: 15.0

Danger



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name	:	Nitrous oxide
SDS no	:	093A
Other means of identification	:	Nitrous oxide CAS-No. : 10024-97-2 EC-No. : 233-032-0 EC Index-No. : ---
REACH registration No	:	01-2119970538-25
Chemical formula	:	N2O

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	:	Industrial and professional uses. Perform risk assessment prior to use. Medical applications.
Uses advised against	:	Do not inhale product on purpose because of the risk of asphyxiation. Do not inhale product on purpose because of the risk of narcotic effects.
Uses other than those listed above are not supported, contact your supplier for more information on other uses.		

1.3. Details of the supplier of the safety data sheet

Company identification	:	Irish Oxygen Co Ltd Waterfall Road T12 PP40 Cork - Ireland T 021-4541821 (Mon-Fri 08:30-17:30) www.solgroup.com sds@irishoxygen.com
E-Mail address (competent person)	:	msds@sol.it

1.4. Emergency telephone number

Emergency telephone number	:	021-4541821 (Mon-Fri 08:30-17:30)
----------------------------	---	-----------------------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Oxidising Gases, Category 1	H270
	Gases under pressure : Liquefied gas	H280
Health hazards	Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
 Reference number: 093A

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS03

GHS04

GHS07

Signal word (CLP) :

Hazard statements (CLP) :

Precautionary statements (CLP) :

- Prevention

- Response

- Storage

Supplemental information

: Danger

: H270 - May cause or intensify fire; oxidiser.
 H280 - Contains gas under pressure; may explode if heated.
 H336 - May cause drowsiness or dizziness.

: P260 - Do not breathe gas, vapours.

P244 - Keep valves and fittings free from oil and grease.

P220 - Keep away from clothing and other combustible materials.

: P304+P340+P315 - IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice / attention.
 P370+P376 - In case of fire: Stop leak if safe to do so.

: P403 - Store in a well-ventilated place.

: Do not inhale product on purpose because of the risk of asphyxiation.

Do not inhale product on purpose because of the risk of narcotic effects.

2.3. Other hazards

Contact with liquid may cause cold burns/frostbite.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	%	Product identifier	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Nitrous oxide	100	CAS-No.: 10024-97-2 EC-No.: 233-032-0 EC Index-No.: --- REACH registration No: 01-2119970538-25	Ox. Gas 1, H270 Press. Gas (Liq.), H280 STOT SE 3, H336

Contains no other components or impurities which will influence the classification of the product.

Not applicable

3.2. Mixtures

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation

: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.

- Skin contact

: In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.

- Eye contact

: Immediately flush eyes thoroughly with water for at least 15 minutes.

- Ingestion

: Ingestion is not considered a potential route of exposure.

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 093A

4.2. Most important symptoms and effects, both acute and delayed

In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination.
See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
Product does not burn, use fire control measures appropriate for the surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Supports combustion.
Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : Nitric oxide/nitrogen dioxide.

5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
If possible, stop flow of product.
Use water spray or fog to knock down fire fumes if possible.
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.
Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel : Act in accordance with local emergency plan.
Try to stop release.
Evacuate area.
Eliminate ignition sources.
Ensure adequate air ventilation.
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
Stay upwind.
See section 8 of the SDS for more information on personal protective equipment.
- For emergency responders : Monitor concentration of released product.
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area.

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 093A

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product

- : Use only lubricants and sealings approved for the specific gas service.
- The product must be handled in accordance with good industrial hygiene and safety procedures.
- Only experienced and properly instructed persons should handle gases under pressure.
- Consider pressure relief device(s) in gas installations.
- Ensure the complete gas system was (or is regularly) checked for leaks before use.
- Do not smoke while handling product.
- Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of Equipment for Oxygen Service downloadable at <http://www.eiga.eu>.
- Use no oil or grease.
- Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
- Avoid suck back of water, acid and alkalis.
- Do not breathe gas.
- Avoid release of product into work area.

For more guidance on safe use, refer to the EIGA Doc.176 "Safe practices for storage and handling of Nitrous oxide", downloadable at <http://www.eiga.org>." and consult your supplier.

Temperatures above 150°C (300°F) shall be avoided by all practical means, to reduce the likelihood of an explosive decomposition of the nitrous oxide.

Clean all surfaces in direct contact with nitrous oxide as for oxygen service.

Nitrous oxide transfer pumps shall be provided with an interlock to prevent dry running.

Use self-limiting heating devices. Direct contact electric immersion heaters are not allowed.

- : Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Protect containers from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Do not remove or deface labels provided by the supplier for the identification of the content of the container.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

Safe handling of the gas receptacle

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Segregate from flammable gases and other flammable materials in store.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 093A

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Nitrous oxide (10024-97-2)	
Ireland - Occupational Exposure Limits	
Local name	Nitrous oxide
OEL TWA [1]	90 mg/m ³
OEL TWA [2]	50 ppm
Regulatory reference	Chemical Agents Code of Practice 2020

Nitrous oxide (10024-97-2)	
DNEL: Derived no effect level (Workers)	
Long-term - systemic effects, inhalation	183 mg/m ³

PNEC (Predicted No-Effect Concentration) : None established.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Product to be handled in a closed system.

Systems under pressure should be regularly checked for leakages.

Ensure exposure is below occupational exposure limits (where available).

Gas detectors should be used when oxidising gases may be released.

Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

- Eye/face protection : Wear goggles when transfilling or breaking transfer connections.
Standard EN 166 - Personal eye-protection - specifications.
- Skin protection : Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.
Wear cold insulating gloves when transfilling or breaking transfer connections.
Standard EN 511 - Cold insulating gloves.
- Hand protection : Consider the use of flame resistant safety clothing.
Standard EN ISO 14116 - Limited flame spread materials.
Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Other

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 093A

- Respiratory protection
 - : Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
 - Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
 - Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
 - Consult respiratory device supplier's product information for the selection of the appropriate device.
 - Gas filters do not protect against oxygen deficiency.
 - Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .
 - Keep self contained breathing apparatus readily available for emergency use.
 - Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
- Thermal hazards
 - : None in addition to the above sections.

8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa

: Gas.

- Colour

: Colourless.

Odour

: Sweetish. Poor warning properties at high concentrations.

Odour threshold is subjective and inadequate to warn of overexposure.

Melting point / Freezing point

: -90.81 °C

: -90.81 °C

: -88.5 °C

Boiling point

: Non flammable.

Flammability

: Not available

Lower explosion limit

: Not available

Upper explosion limit

: Not available

Flash point

: Not applicable for gases and gas mixtures.

Auto-ignition temperature

: Non flammable.

Decomposition temperature

: Not applicable.

pH

: Not applicable for gases and gas mixtures.

Viscosity, kinematic

: No reliable data available.

Water solubility [20°C]

: 1500 mg/l

Partition coefficient n-octanol/water (Log Kow)

: Not available

Vapour pressure [20°C]

: 50.8 bar(a)

Vapour pressure [50°C]

: Not applicable.

Density and/or relative density

: Not applicable.

Relative vapour density (air=1)

: 1.5

Particle characteristics

: Not applicable.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Explosive properties

: Not applicable.

Explosion limits

: Non flammable.

Oxidising properties

: Oxidiser.

- Coefficient of oxygen equivalency (Ci)

: 0.6

Critical temperature [°C]

: 36.4 °C

9.2.2. Other safety characteristics

Molar mass

: 44 g/mol

Evaporation rate

: Not applicable for gases and gas mixtures.

Gas group

: Press. Gas (Liq.).

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 093A

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.
At temperatures over 575°C and at atmospheric pressure, nitrous oxide decomposes into nitrogen and oxygen.
In the presence of catalysts (e.g. halogen products, mercury, nickel, platinum) the rate of decomposition increases and decomposition can occur at even lower temperatures.
Nitrous oxide dissociation is irreversible and exothermic, leading to a considerable rise in pressure.

10.3. Possibility of hazardous reactions

Violently oxidises organic material.

10.4. Conditions to avoid

Avoid moisture in installation systems.

10.5. Incompatible materials

Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of Equipment for Oxygen Service downloadable at <http://www.eiga.eu>.
May react violently with combustible materials.
May react violently with reducing agents.
For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	: Classification criteria are not met.
LC50 Inhalation - Rat [ppm]	500000 ppm/4h
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Hemotoxic effect. Neurologic effect. At low concentrations: Central nervous system. Erythrocytes. Kidneys. liver.
Target organ(s)	



Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 093A

Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information : Inhalation causes narcotic effects.

SECTION 12: Ecological information

12.1. Toxicity

Assessment : No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l] : No data available.
EC50 72h - Algae [mg/l] : No data available.
LC50 96 h - Fish [mg/l] : No data available.

12.2. Persistence and degradability

Assessment : Not applicable for inorganic products.
Study scientifically unjustified.

12.3. Bioaccumulative potential

Assessment : Not expected to bioaccumulate due to the low log Kow (log Kow < 4).
See section 9.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.
Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Endocrine disrupting properties

Assessment :

12.7. Other adverse effects

Other adverse effects : No known effects from this product.
Effect on the ozone layer : No effect on the ozone layer.
Global warming potential [CO₂=1] : 298
Effect on global warming : When discharged in large quantities may contribute to the greenhouse effect.
Contains greenhouse gas(es).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required.

Discharge to atmosphere in large quantities should be avoided.

Do not discharge into any place where its accumulation could be dangerous.

Ensure that the emission levels from local regulations or operating permits are not exceeded.

Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.

Return unused product in original container to supplier.

: 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
 Reference number: 093A

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN

UN-No. : 1070

14.2. UN proper shipping name


Transport by road/rail (ADR/RID) : NITROUS OXIDE

Transport by air (ICAO-TI / IATA-DGR) : Nitrous oxide

Transport by sea (IMDG) : NITROUS OXIDE

14.3. Transport hazard class(es)

Labelling



2.2 : Non-flammable, non-toxic gases.

5.1 : Oxidizing substances.

Transport by road/rail (ADR/RID)

Class : 2

Classification code : 2O

Hazard identification number : 25

Tunnel Restriction : C/E - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other carriage : Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2 (5.1)

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2 (5.1)

Emergency Schedule (EmS) - Fire : F-C

Emergency Schedule (EmS) - Spillage : S-W

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable.

Transport by air (ICAO-TI / IATA-DGR) : Not applicable.

Transport by sea (IMDG) : Not applicable.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.

Transport by air (ICAO-TI / IATA-DGR) : None.

Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200.

Transport by air (ICAO-TI / IATA-DGR) : P200.

Passenger and Cargo Aircraft : 200.

Cargo Aircraft only : 200.

Transport by sea (IMDG) : P200.

Special transport precautions

: Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:

- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.



Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 093A

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use	: None.
Other information, restriction and prohibition regulations	: Not listed on the PIC list (Regulation EU 649/2012).
Seveso Directive : 2012/18/EU (Seveso III)	: Covered.

National regulations

Regulatory reference	: Ensure all national/local regulations are observed.
----------------------	---

15.2. Chemical safety assessment

A CSA has been carried out.

SECTION 16: Other information

Indication of changes	: Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.
Abbreviations and acronyms	: ATE - Acute Toxicity Estimate. CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008. REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. EINECS - European Inventory of Existing Commercial Chemical Substances. CAS# - Chemical Abstract Service number. PPE - Personal Protection Equipment. LC50 - Lethal Concentration to 50 % of a test population. RMM - Risk Management Measures. PBT - Persistent, Bioaccumulative and Toxic. vPvB - Very Persistent and Very Bioaccumulative. STOT- SE : Specific Target Organ Toxicity - Single Exposure. CSA - Chemical Safety Assessment. EN - European Standard. UN - United Nations. ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road. IATA - International Air Transport Association. IMDG code - International Maritime Dangerous Goods. RID - Regulations concerning the International Carriage of Dangerous Goods by Rail. WGK - Water Hazard Class. STOT - RE : Specific Target Organ Toxicity - Repeated Exposure. UFI : Unique Formula Identifier.
Training advice	: None.
Further information	: Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP). Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at http://www.Eiga.eu .

Full text of H- and EUH-statements	
H270	May cause or intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.
H336	May cause drowsiness or dizziness.
Ox. Gas 1	Oxidising Gases, Category 1



Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 093A

Press. Gas (Liq.)	Gases under pressure : Liquefied gas
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
Details given in this document are believed to be correct at the time of going to press.
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 093A

Annex to the safety data sheet

This Annex documents the Exposure Scenarios (ESs) related to the identified uses of the registered substance. The ESs detail protective measures for workers and the environment in addition to those described in sections 7, 8, 11, 12 and 13 of the SDS that are required to ensure that the potential exposure to workers and the environment remains within acceptable levels for each of the identified uses.

Table of contents of the Annex

Identified Uses	Es N°	Short title	Page
Feedstock in chemical processes	EIGA093-1	Industrial uses, closed contained conditions	13
Formulation of mixtures in pressure receptacles	EIGA093-1	Industrial uses, closed contained conditions	13
Transfilling in pressure receptacles	EIGA093-1	Industrial uses, closed contained conditions	13
Calibration of analysis equipment	EIGA093-1	Industrial uses, closed contained conditions	13
Refilling of refrigeration equipment	EIGA093-1	Industrial uses, closed contained conditions	13
Electronic component manufacture	EIGA093-1	Industrial uses, closed contained conditions	13
Pressure gas in airbag inflators	EIGA093-1	Industrial uses, closed contained conditions	13
Aerosol propellant.	EIGA093-2	Professional uses in open conditions.	19

Exposure scenario

Nitrous oxide

Annex to the safety data sheet

Reference number: 093A

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

1. EIGA093-1: Industrial uses, closed contained conditions

1.1. Title section

Industrial uses, closed contained conditions

ES Ref.: EIGA093-1	
Revision date: 31/01/2017	

Processes, tasks, activities covered	Industrial uses, including product transfers and associated laboratory activities within different closed or contained systems
--------------------------------------	--

Environment	Use descriptors
CS1	

Worker	Use descriptors
CS2	
CS3	
CS4	
CS5	

Assessment method	MEASE EUSES v2.1
-------------------	---------------------

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure:

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)	
Annual site tonnage:	250
Emission Days (days/year)	365

Technical and organisational conditions and measures	
Soil emission controls are not applicable as there is no direct release to soil. No additional requirement	
Ensure operatives are trained to minimise releases	

Exposure scenario

Nitrous oxide

Annex to the safety data sheet

Reference number: 093A

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

Conditions and measures related to sewage treatment plant

Wastewater emission controls are not applicable as there is no direct release to wastewater

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS. No additional information

Other conditions affecting environmental exposure

No additional information

1.2.2. Control of worker exposure:

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Duration of task

≤ 8 h/day

Exposure duration

Occasional exposure, e.g. during maintenance and sampling, connecting/ disconnecting containers .

Covers frequency up to:

5 days/week

Technical and organisational conditions and measures

Handle product within a closed system

During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.

Fill containers at dedicated fill points supplied with local extract ventilation.

Ensure samples are obtained under containment or extract ventilation.

Drain down and flush system prior to equipment break-in or maintenance.

Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

See sections 2 and 7 of the SDS.

Ensure operatives are trained to minimise exposure

Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Exposure scenario

Nitrous oxide

Annex to the safety data sheet

Reference number: 093A

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection measures have to be applied in case of potential exposure only.

See section 8 of the SDS.

Other conditions affecting workers exposure

Indoor use

1.2.3. Control of worker exposure:

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Duration of task	≤ 8 h/day
Exposure duration	Occasional exposure, e.g. during maintenance and sampling, connecting/ disconnecting containers .
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
See sections 2 and 7 of the SDS.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection measures have to be applied in case of potential exposure only.

See section 8 of the SDS.



Exposure scenario

Nitrous oxide

Annex to the safety data sheet

Reference number: 093A

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

Other conditions affecting workers exposure

Indoor use

1.2.4. Control of worker exposure:

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Duration of task	≤ 8 h/day
Exposure duration	Occasional exposure, e.g. during maintenance and sampling, connecting/ disconnecting containers .
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
See sections 2 and 7 of the SDS.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection measures have to be applied in case of potential exposure only.

See section 8 of the SDS.

Other conditions affecting workers exposure

Indoor use



Exposure scenario

Nitrous oxide

Annex to the safety data sheet

Reference number: 093A

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

1.2.5. Control of worker exposure:

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %
Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Duration of task	≤ 8 h/day
Exposure duration	Occasional exposure, e.g. during maintenance and sampling, connecting/ disconnecting containers .
Covers frequency up to:	5 days/week
Technical and organisational conditions and measures	
Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
See sections 2 and 7 of the SDS.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection measures have to be applied in case of potential exposure only.	
See section 8 of the SDS.	
Other conditions affecting workers exposure	
Indoor use	

Exposure scenario

Nitrous oxide

Annex to the safety data sheet

Reference number: 093A

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure:

The exposure of aquatic, terrestrial, sediment and sewage treatment microorganisms is considered to be negligible because the substance partitions primarily to air when released to the environment. The resulting environmental exposure is not expected to add significantly to already present background levels of the gas in the environment

1.3.2. Worker exposure:

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Inhalation - Long-term - systemic effects	0.018 mg/m ³	Indoor use , General ventilation, Without LEV, MEASE	0

1.3.3. Worker exposure:

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Inhalation - Long-term - systemic effects	14.937 mg/m ³	Indoor use , General ventilation, Without LEV, MEASE	0.082

1.3.4. Worker exposure:

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Inhalation - Long-term - systemic effects	37.342 mg/m ³	Indoor use , General ventilation, Without LEV, MEASE	0.204

1.3.5. Worker exposure:

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Inhalation - Long-term - systemic effects	74.683 mg/m ³	Indoor use , General ventilation, Without LEV, MEASE	0.408

1.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

1.4.1. Environment

Guidance - Environment	Check that RMMs and OCs are as described above or of equivalent efficiency
------------------------	--

1.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : MEASE model available at: http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php
-------------------	--

Exposure scenario

Nitrous oxide

Annex to the safety data sheet

Reference number: 093A

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

2. EIGA093-2: Professional uses in open conditions.

2.1. Title section

Professional uses in open conditions.

ES Ref.: EIGA093-2
Revision date: 31/01/2017

Processes, tasks, activities covered	Professional uses of a processing aid in non-industrial settings.
--------------------------------------	---

Environment	Use descriptors
CS1	

Worker	Use descriptors
CS2	

Assessment method	ConsExpo EUSES v2.1
-------------------	------------------------

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure:

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)	
No additional information	

Technical and organisational conditions and measures	
Ensure operatives are trained to minimise exposure	

Conditions and measures related to sewage treatment plant	
No additional information	

Conditions and measures related to treatment of waste (including article waste)	
See section 13 of the SDS. No additional information	

Exposure scenario

Nitrous oxide

Annex to the safety data sheet

Reference number: 093A

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

Other conditions affecting environmental exposure

No additional information	

2.2.2. Control of worker exposure:

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

Maximum daily site tonnage	0.5
Duration of task	≤ 8 h/day
Exposure duration	Individual events, not totalling more than 1hour, per working day.

Technical and organisational conditions and measures

General ventilation	
See sections 2 and 7 of the SDS.	
Ensure operatives are trained to minimise exposure. Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

See section 8 of the SDS. Personal protection measures have to be applied in case of potential exposure only.	
---	--

Other conditions affecting workers exposure

Indoor use	
------------	--

2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure:

The exposure of aquatic, terrestrial, sediment and sewage treatment microorganisms is considered to be negligible because the substance partitions primarily to air when released to the environment. The resulting environmental exposure is not expected to add significantly to already present background levels of the gas in the environment
--

2.3.2. Worker exposure:

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Acute - Local - Inhalation	158 mg/m ³	Indoor use , General ventilation, Without LEV, ConsExpo	

Exposure scenario

Nitrous oxide

Annex to the safety data sheet

Reference number: 093A

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

2.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

2.4.1. Environment

Guidance - Environment	Check that RMMs and OCs are as described above or of equivalent efficiency
------------------------	--

2.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : ConsExpo model available at: http://www.rivm.nl/en/Topics/Topics/C/ConsExpo/Spray_model
-------------------	--

End of document